

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name ZENOX MOLY CHAIN LUBE (AEROSOL)

Synonyms CHAIN LUBE • Z017 - PART NUMBER

1.2 Uses and uses advised against

Uses CHAIN LUBRICANT • GEAR LUBRICANT • LUBRICANT • LUBRICANT - AEROSOL

1.3 Details of the supplier of the product

Supplier name	ZENOX LUBRICANTS
Address	PO Box 3189, Yokine, WA, 6060, AUSTRALIA
Telephone	1800 4 93669
Email	info@zenox.com.au
Website	http://www.zenox.com.au

1800 4 93669

1.4 Emergency telephone numbers

Emergency

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Aerosols - Flammable: Category 1 Aerosols - Pressurised: Category 1

Health Hazards

Aspiration Hazard: Category 1 Skin Corrosion/Irritation: Category 2 Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects) Toxic to Reproduction: Category 2 Specific Target Organ Toxicity (Repeated Exposure): Category 2

Environmental Hazards

Aquatic Toxicity (Chronic): Category 2

2.2 GHS Label elements

Signal word Pictograms





Hazard statements	
H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Prevention statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response statements

	Concer spinage.
P391	Collect spillage.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P331	Do NOT induce vomiting.
P321	Specific treatment is advised - see first aid instructions.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
-	

Storage statements

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Disposal statements

Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

P501

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
BUTANE	106-97-8	203-448-7	<40%
N-HEXANE	110-54-3	203-777-6	20 to 40%
PROPANE	74-98-6	200-827-9	<15%
GRAPHITE	7782-42-5	231-955-3	<10%
MOLYBDENUM DISULPHIDE	1317-33-5	215-263-9	<10%
RESIDUAL OILS, PETROLEUM, SOLVENT DEASPHALTED (<3% DMSO EXTRACT)	64741-95-3	265-096-0	10 to 30%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If

ChemAlert.

swallowed, do not induce vomiting.

First aid facilities Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, etc when handling.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

2Y

- 2 Fine Water Spray.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (< 50°C), dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/ leaking containers. Large storage areas should have appropriate fire protection systems.

7.3 Specific end uses

No information provided.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m³	ppm	mg/m³
Butane	SWA [AUS]	800	1900		
Butane	SWA [Proposed]			1000	2370
Graphite (all forms except fibres)	SWA [AUS]		3		
Insoluble Molybdenum compounds	SWA [AUS]		10		
Propane	SWA [AUS]	Asphyxiant			
n-Hexane	SWA [AUS]	20	72		

Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
N-HEXANE	ACGIH BEI	2,5-Hexanedione in urine (without hydrolysis)	End of shift	0.5 mg/L

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flashback.

PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear PVA or viton® gloves.
Body	With prolonged use, wear coveralls.

Respiratory Where an inhalation risk exists, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator. At high vapour levels, wear an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

internation on bable physical a	
Appearance	VISCOUS BLACK PASTE (AEROSOL DISPENSED)
Odour	SLIGHT SWEET ODOUR
Flammability	EXTREMELY FLAMMABLE
Flash point	-30°C (cc)
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	0.70 to 0.75
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	7.5 %
Lower explosion limit	1.2 %
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

ChemAlert.

9.2 Other information % Volatiles

24 %

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerisation is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Information available for the ingredients:

		Ouel I DES	De muerte DES		
Ingredient		Oral LD50	Dermal LD50	Inhalation LC50	
BUTANE		Study not feasible	Study not feasible	658000 mg/m3/4H (rat)	
N-HEXANE		25 g/kg (rat)	3000 mg/kg (rabbit)	48000 ppm/4 hours (rat)	
PROPANE		Study not feasible	Study not feasible	> 800000 ppm/15M (rat)	
MOLYBDENUM DIS	SULPHIDE			> 2820 mg/m³ (rat) (4 hours)	
Skin	Contact may result in drying	Contact may result in drying and defatting of the skin, irritation, rash and dermatitis.			
Eye	Contact may cause discomfort, lacrimation and redness.				
Sensitisation	Not classified as causing sk	Not classified as causing skin or respiratory sensitisation.			
Mutagenicity	Insufficient data available to classify as a mutagen.				
Carcinogenicity	Insufficient data available to classify as a carcinogen.				
Reproductive	n-Hexane is suspected of damaging fertility. Effects on experimental animals includes testicular and epididymal lesions with possible irreversible sterility.				
STOT - single exposure	Over exposure may result in irritation of the nose and throat, coughing, nausea and headache. High level exposure may result in dizziness, drowsiness, breathing difficulties and unconsciousness.				
STOT - repeated exposure	Repeated exposure to n-Hexane may result in damage to the peripheral nervous system, with numbness, tingling, muscle damage, and reduced mobility of the limbs.				
Aspiration		unlikely due to product form. However, if liquid component is ingested, aspiration into emical pneumonitis and pulmonary oedema.			

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

n-Hexane is expected to exist entirely in the vapour-phase in ambient air. Biodegradation of n-hexane may occur in soil and water, however volatilisation and adsorption are expected to be far more important fate processes.



12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

In aquatic systems n-hexane may partition from the water column to organic matter contained in sediments and suspended materials.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposalFor small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. Do not
puncture or incinerate aerosol cans. Contact the manufacturer/supplier for additional information (if required).LegislationDispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1950	1950	1950
14.2 Proper Shipping Name	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport hazard class	2.1	2.1	2.1
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Marine Pollutant.

14.6 Special precautions for user

Hazchem code	2Y
GTEPG	2D1
EmS	F-D, S-U

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture			
Poison schedule	Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).		
Classifications	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).		
Inventory listings	AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt.		

16. OTHER INFORMATION

Additional information AEROSOL CANS may explode at temperatures approaching 50°C.



PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Δ	h	h	re	vi	ia	fi	ი	n	S
	N	ν	16	V.	a	u	v		-

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists		
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds		
	CNS	Central Nervous System		
	EC No.	EC No - European Community Number		
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)		
	GHS	Globally Harmonized System		
	GTEPG	Group Text Emergency Procedure Guide		
	IARC	International Agency for Research on Cancer		
	LC50	Lethal Concentration, 50% / Median Lethal Concentration		
	LD50	Lethal Dose, 50% / Median Lethal Dose		
	mg/m³	Milligrams per Cubic Metre		
	OEL	Occupational Exposure Limit		
	рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).		
	ppm	Parts Per Million		
	STEL	Short-Term Exposure Limit		
	STOT-RE	Specific target organ toxicity (repeated exposure)		
	STOT-SE	Specific target organ toxicity (single exposure)		
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons		
	SWA	Safe Work Australia		
	TLV	Threshold Limit Value		
	TWA	Time Weighted Average		
Report status	This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').			
	It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.			
	not provide no liability	has taken all due care to include accurate and up-to-date information in this SDS, it does any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts for any loss, injury or damage (including consequential loss) which may be suffered or any person as a consequence of their reliance on the information contained in this SDS.		
Prepared by	5 Ventnor A Western Au	ement Technologies ve, West Perth stralia 6005 8 9322 1711		

[End of SDS]

Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmtglobal.com